

Vertical AC unit (with Heat)



General:

Manufacturer Unit Model Number

Blower fan Air Connections:

Certification

Single Point Power Supply

Connections

Full Load Amps Cooling Full Load Amps Htg Mode

Unit MCA Unit MFS

Unit Dimensions

Unit Ship Weight

Smart Family of Cooling Products

SAVP10Q 3hp

20" round duct or diffusers ETL, UL 1995 - CSA 236 STD 22.2

460V/3PH/60HZ

Single point Series 16 Cam-Lok connections

23.9 A 64 A (460V)*

78 A* 100 A*

66"L x 35"W x 98"H

2,200 lbs

^{*} Data shown with 32kW of integral heat



Package Vertical A/C Unit

Unit Features:

- Unit comes with 20" round supply and return duct connections (with duct doors) OR bolt on supply diffusers and return louvers
- Scroll compressor with installed suction accumulators
- Direct drive High Static plenum fan
- ULTRA-Low Noise design
- Variable speed condenser & evaporator fans to allow for running at lowest sound levels possible
- Rated cooling air flow of 4,000 cfm
- Air flow range of 2,000 5,000 cfm
- Hydrophilic coated, non-lanced condenser fins
- Hydrophilic coated evaporator fins
- Stainless steel hardware
- Stainless Steel drain pan
- Permanently installed drain pan P-trap (protected within unit base)
- Integral heat package:
 - Available with 16 or 32kW of heat
 - Stainless steel sheathed, hermetically sealed, finned tubular heating elements

Unit Drawings:

