

Vertical AC unit (with Heat)



General:

Manufacturer Unit Model Number Blower fan

Air Connections:

Certification

Single Point Power Supply

Connections

Full Load Amps Cooling

Full Load Amps Htg Mode

Unit MCA Unit MFS

Unit Dimensions Unit Ship Weight **Smart Family of Cooling Products**

SAVP21Q (2) 5hp

Return air Louvers and 20" Round collars Supply air Diffuser and 20" Round collars

ETL, UL 1995 - CSA 236 STD 22.2

460V/3PH/60HZ

Single point Series 16 Cam-Lok connections

44.6 A

124.6 A (460V)*

152 A* 200 A*

92"L x 44"W x 99"H

5,000 lbs

^{*} Data shown with 64kW of integral heat



Package Vertical A/C Unit

Unit Features:

- Unit comes with BOTH 20" round supply and return duct connections (with duct doors) as well as bolt on supply diffusers and return louvers
- Scroll compressor with installed suction accumulators
- Direct drive High Static plenum fan
- ULTRA-Low Noise design
- Variable speed condenser & evaporator fans to allow for running at lowest sound levels possible
- Rated cooling air flow of 6,500 cfm
- Air flow range of 4,000 8,000 cfm
- Hydrophilic coated, non-lanced condenser fins
- Hydrophilic coated evaporator fins
- Stainless steel hardware
- Stainless Steel drain pan
- Permanently installed drain pan P-trap (protected within unit base)
- Integral heat package:
 - Available with 32 or 64kW of heat
 - Stainless steel sheathed, hermetically sealed, finned tubular heating elements

Unit Drawings:

