



AIR COMPRESSORS - OIL-FREE - ELECTRIC

CAT CLASS	ITEM	RANGE	WEIGHT	TRANSPORT	POWER
230-4000	1,580 CFM @ 150 PSIG	~1,590 - 1,580 ACFM @ 100 - 150 PSIG	13,500 lb	Skid Mounted	460V 3Ø (60 Hz) • ~510 AMP max
230-2000	809 CFM @ 135 PSIG	~815 - 809 ACFM @ 100 - 150 PSIG	8,700 lb	Skid Mounted	460V 3Ø (60 Hz) • ~265 AMP max
230-1000	400 CFM @ 135 PSIG	~403 - 400 ACFM @ 100 - 135 PSIG	5,000 lb	Skid Mounted	460V 3Ø (60 Hz) • ~145 AMP max



AIR COMPRESSORS - OIL-FREE - DIESEL

CAT CLASS	ITEM	RANGE	WEIGHT	TRANSPORT	EMISSIONS
220-2000	1,560 CFM @ 150 PSIG	~1,564 - 1560 ACFM @ 100 - 150 PSIG	22,500 lb	Pintle	Tier 4 Final Diesel



AIR COMPRESSORS - PORTABLE - DIESEL

CAT CLASS	ITEM	EMISSIONS	WEIGHT	TRANSPORT
210-2500	1,600 CFM @ 100 - 150 PSIG	Tier 4 Final	19,085 lb	Tow-Behind
210-2500	1,600 CFM @ 100 - 150 PSIG	Tier 3	16,216 lb	Tow-Behind
215-1800	1,350 / 1,550 CFM @ 508 - 246 PSIG	Tier 4 Final	19,225 lb	Tow-Behind
215-1700	900 / 1,150 CFM @ 500 - 350 PSIG	Tier 3	18,980 lb	Tow-Behind
210-2100	800 / 900 CFM @ 200 - 150 PSIG	Tier 4 Final	11,750 lb	Tow-Behind
210-1650	400 CFM @ 200 PSIG	Tier 4 Final	4,840 lb	Tow-Behind
210-1600	375 CFM @ 200 PSIG	Varies by model	4,440 lb	Tow-Behind

Air Compression - Electric/Oil Free
1580 CFM@150 PSIG





AIR HANDLING UNITS

CAT CLASS	ITEM	AIR FLOW	WEIGHT
560-0230	230 Ton	10,000 - 35,000 CFM	10,000 lb
560-0150	150 Ton - High Static	14,000 - 30,000 (S)CFM	4,025 lb
560-0120	120 Ton	4,500 - 20,000 CFM	5,000 lb
560-0060	60 Ton	4,000 - 13,000 CFM	4,000 lb



DESICCANT DRYERS - INTEGRATED AFTERCOOLER & FILTRATION

CAT CLASS	ITEM	MAX PRESSURE	PRESSURE DEW POINT	WEIGHT
260-2800	Up to 350 PSIG - 2,800 CFM Class	350 PSIG	-40°F (std); -100°F (optional)	7,800 lb
260-1800	Up to 350 PSIG - 1,800 CFM Class	350 PSIG	-40°F (std); -100°F (optional)	5,700 lb
270-3000	Up to 150 PSIG - 3,000 CFM Class	150 PSIG	-40°F (std); -100°F (optional)	10,150 lb
270-1600	Up to 150 PSIG - 1,600 CFM Class	150 PSIG	-40°F (std); -100°F (optional)	6,200 lb
270-1000	Up to 150 PSIG - 1,000 CFM Class	150 PSIG	-40°F (std); -100°F (optional)	4,000 lb
250-0500	Up to 150 PSIG - 500 CFM Class	150 PSIG	-40°F (std); -100°F (optional)	2,325 lb



AIR RECEIVER

CAT CLASS	ITEM	CONFIGURATION	WEIGHT
940-6000	3,000 GAL / 165 PSIG	Skid Mounted	9,600 lb



AIR BOOSTERS - ELECTRIC

CAT CLASS	ITEM	INPUT	CONFIGURATION	POWER	WEIGHT
941-5000	1,000 CFM @ 600 PSIG	1,600 CFM @ 120 PSI	Skid Mounted	400 AMP, 480 V	18,700 lb



MOBILE GENERATORS - LARGE

CAT CLASS	ITEM	VOLTAGE / PHASE	WEIGHT	HITCH TYPE
530-1550	2,000 kW (2500 kVA) Tier 4F	480V 3Ø (60 Hz)	99,344 lb	Fifth Wheel
530-1500	2,000 kW (2,500 kVA)	480V 3Ø (60 Hz)	93,000 lb	Fifth Wheel
530-1400	1,500 kW (1,875 kVA)	480V 3Ø (60 Hz)	59,000 lb	Fifth Wheel
530-1300	1,000 kW (1,250 kVA)	480/277V / 208/120V 3Ø (60 Hz)	56,200 lb	Fifth Wheel
530-1200	800 kW (1,000 kVA)	480/277V / 208/120V 3Ø (60 Hz)	46,547 lb	Fifth Wheel



MOBILE GENERATORS - MID-RANGE

CAT CLASS	ITEM	VOLTAGE / PHASE	WEIGHT	HITCH TYPE
530-1100	500 kW (625 kVA)	480/277V / 208/120V 3Ø (60 Hz)	39,350 lb	Fifth Wheel
530-1000	400 kW (500 kVA)	480/277V / 208/120V 3Ø (60 Hz)	21,300 lb	Pintle
520-2600	350 kW (437.5 kVA)	480/277V / 208/120V 3Ø (60 Hz)	22,130 lb	Pintle
520-2500	300 kW (375 kVA)	480/277V / 208/120V 3Ø (60 Hz)	16,550 lb	Pintle
520-2450	250 kW (330 kVA)	480/277V / 208/120V 3Ø (60 Hz)	14,881 lb	Pintle
520-2400	200 kW (250 kVA)	480/277V / 208/120V 3Ø (60 Hz) • 240/120V 1Ø (60 Hz)	13,860 lb	2 5/16" Ball



MOBILE GENERATORS - SMALL

CAT CLASS	ITEM	VOLTAGE / PHASE	WEIGHT	HITCH TYPE
520-2100	125 kW (156 kVA)	480/277V / 208/120V 3Ø (60 Hz) • 240/120V 1Ø (60 Hz)	8,488 lb	2 5/16" Ball
520-2000	100 kW (125 kVA)	480/277V / 208/120V 3Ø (60 Hz) • 240/120V 1Ø (60 Hz)	6,800 lb	2 5/16" Ball
520-1500	55 kW (68 kVA)	480/277V / 208/120V 3Ø (60 Hz) • 240/120V 1Ø (60 Hz)	6,980 lb	2 5/16" Ball
520-1400	45 kW (56 kVA)	480/277V / 208/120V 3Ø (60 Hz) • 240/120V 1Ø (60 Hz)	3,930 lb	2 5/16" Ball
520-1300	30 kW (37 kVA)	480/277V / 208/120V 3Ø (60 Hz) • 240/120V 1Ø (60 Hz)	2,970 lb	2 5/16" Ball

Get a custom consult. **844.660.RENT (7368)**

PANELS & SWITCHGEAR



CAT CLASS	ITEM	PHASE / WIRE	CONFIGURATION
946-9120	12,000 AMP Common Bus Panel	3-Phase	Skid
946-4080	3,000 AMP I-Line Panel	3-Phase	Skid
946-4020	1,200 AMP I-Line Panel	3-Phase	Skid
946-2320	600 AMP Cam Breakout	3-Phase	Portable
946-2310	400 AMP Multibox	3-Phase	Hand-Carry
946-2290	100-200 AMP QBS Panels	3-Phase	Hand-Carry

TRANSFORMERS



CAT CLASS	ITEM	PRIMARY VOLTAGE	SECONDARY VOLTAGE	PHASE / WIRE	CONFIGURATION
946-5120	2,500 kVA	2.4 / 4.16 kV or 7.2 / 12.47 kV	480Y / 277 V	3-Phase	Skid
946-5040	500 kVA	480 V	208Y / 120 V	3-Phase	Skid
946-5020	150 kVA	480 V	208Y / 120 V	3-Phase	Skid
946-5010	75 kVA	480 V	208Y / 120 V	3-Phase	Skid

DISCONNECTS



CAT CLASS	ITEM	FREQUENCY	BREAKER TYPE	PHASE / WIRE
6000	6,000 AMP	60 Hz	Adjustable to 1600 amps	3-Phase
3000	3,000 AMP	60 Hz	Adjustable to 800 amps	3-Phase

CABLING & ACCESSORIES



CAT CLASS	ITEM	SPECS
946-1880	Medium Voltage (MV) Cable	50' or 100' sections
946-1810	4/0 Cable	50' sections
946-1900	2/5 Banded Cable	50' sections
946-1705	Quad Stringers	50' stringer
946-1710	Extensions	50' or 100' extensions

LOAD BANKS



CAT CLASS	ITEM	VOLTAGE	WEIGHT	CONFIGURATION
948-2000	2,000 kW	240/480 V	3,200 lb	Trailer Mounted
948-1000	1,000 kW	240/480 V	1,750 lb	Trailer Mounted
948-0400	400 kW	240/480 V	800 lb	Portable
948-0100	100 kW	240/480 V	64 lb	Portable

AUTOMATIC TRANSFER SWITCHES (ATS)



CAT CLASS	ITEM	TRANSITION TYPE	CONFIGURATION
946-8300	3,000 AMP	4P - Open transition	Cage w/ Fork Pockets
946-8160	1,600 AMP	3P - Open transition	Cage w/ Fork Pockets
946-8120	1,200 AMP	3P - Open transition	Cage w/ Fork Pockets



CHILLERS

CAT CLASS	ITEM	LENGTH	WIDTH	HEIGHT	WEIGHT
565-0527	527 Ton	52'	8'	13' 6"	48,500 lb
565-0400	400 Ton	48'	8'	13' 6"	32,000 lb
565-0200	200 Ton	25'	8' 3"	8' 5"	18,720 lb
565-0100	100 Ton	13' 4"	8'	8' 5"	8,280 lb
565-0058	58 Ton	9' 11"	8' 1"	8' 6"	5,860 lb



INDUSTRIAL & EVENT AIR CONDITIONERS

CAT CLASS	ITEM	AIR FLOW	WEIGHT
555-0800	80 Ton	13,000 - 23,000 CFM	4,800 lb
555-0400	40 Ton	3,200 - 9,200 CFM	4,620 lb
555-0300	30 Ton	10,000 - 14,000 CFM	2,250 lb
552-0120	12 Ton	4,050 CFM	1,200 lb



INDUSTRIAL & EVENT AIR CONDITIONERS - WITH HEAT

CAT CLASS	ITEM	AIR FLOW	WEIGHT
554-0250	25 Ton	3,500 - 10,000 CFM	5,000 lb
554-0200	20 Ton	4,000 - 8,000 CFM	5,000 lb
554-0100	10 Ton	2,000 - 5,000 CFM	2,200 lb

Industrial Air Conditioner

80 Ton



Chiller
400 Ton



Schedule your site assessment today.

Contact the location closest to you:

North Texas

Dallas/Fort Worth
353 Long Creek
Sunnyvale, Texas 75182

Central Texas

San Antonio & Austin
120 Industrial Drive
Cibolo, Texas 78108

South Texas

Corpus Christi
1325 S. Padre Island Drive
Corpus Christi, Texas 78416

Need help outside of these regions? Call us today.

844.660.RENT (7368)

HoltIndustrialRentals.com

Power. Compressed Air. Temperature Control.



***HOLT Industrial
Rentals***



Solutions Built on Trust
Power. Compressed Air. Temperature Control.

Providing rental solutions for industrial manufacturing, oil & gas, petrochemical, data centers, construction, mining, and everything in between. Rely on us for emergency response, planned outages, contingency planning, and enhancing productivity.

Call us today.
844.660.RENT (7368)



BATTERY ENERGY STORAGE SYSTEM (BESS)

CAT CLASS	ITEM	FREQUENCY	VOLTAGE	WEIGHT	CONFIGURATION
536-1700	1,000 kW / 1,232 kWh	60 Hz	480 V	55,125 lb	Trailer Mounted
536-1600	1,000-1,260 kW / 672 kWh	60 Hz	480 V	41,282 lb	Trailer Mounted
536-1500	500 kW / 246 kWh	60 Hz	480 V	22,250 lb	Skid
536-1250	250 kW / 575 kWh	60 Hz	480 V	24,250 lb	Skid
536-1120	120 kW / 122.8 kWh	60 Hz	480/208 V	7,650 lb	Skid
536-0200	2 kW / 2.16 kWh	60 Hz	120 V	84 lb	Portable



FUEL TANKS

CAT CLASS	ITEM	LENGTH	WIDTH	HEIGHT	EMPTY WEIGHT
710-5000	5,000 Gallon	19' 11"	8' 00"	9' 06"	14,447 lb
710-3000	3,000 Gallon	9' 10"	8' 00"	9' 06"	9,129 lb
710-2200	2,300 Gallon	8' 03"	7' 06"	8' 03"	7,553 lb
710-1000	1,000 Gallon	7' 07"	7' 07"	4' 04"	3,703 lb
710-0500	500 Gallon	7' 06"	3' 09"	4' 04"	1,814 lb

INSIDE / OUTSIDE / BIG / SMALL

Complete solutions to keep your site running.

Battery Energy Storage System

1,000 kW / 1,232 kWh



Battery Energy Storage System

120 kW / 122.8 kWh